

ULUF SERIES

- Dual refrigeration system
- Direct cooling for higher temperature uniformity
- Excellent temperature stability
- Filterless construction
- Insulated inner doors
- Castors
- Lock on door
- Ergonomic loading
- Heated door frame
- Heated vacuum valve
- 100% HCFC/CFC free

ALL STANDARD FEATURES

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Prepared for GSM alarm
- Prepared for connection of 2 additional probes
- Auto cycle in case of probe failure
- Ambient temperature display
- Direct download of logged data on USB memory stick
- Direct upload of new software via USB memory stick
- 3-level password protected
- Battery level indication
- Display text available in different languages
- Temperature graph
- Integrated data logger
- RS485/RS232 interface
- Integrated memory for 20 years
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Shows all alarms

ULUF 590

Arctiko is proud to present the true dual refrigeration system. By installing two separate cooling systems, this range adds a new dimension to your security. In the unlikely event that one system should fail, the freezer will still maintain -86°C until the problem is solved.

- 90 °C



Battery backup - 72 hours ←

Integrated data logger with memory ←

RS485/RS232 interface ←

On/off protection ←


MODEL	ULUF 590
Item code	DAI 1376
Dimensions exterior WxDxH (mm)	920x885x1990
Capacity (L)	556
Temperature range (°C)	$-90^{\circ}\text{C}/-40^{\circ}\text{C}$
Power supply (V)	230
Frequency (Hz)	50/60

ARCTIKO

The art of simplicity®

Technical specifications

Item code	DAI 1376
Dimensions exterior WxDxH (mm)	920x885x1990
Capacity (L)	556
Dimensions interior WxDxH (mm)	680x608x1345
Insulation (mm)	120
Temperature range (°C)	-90°C/-40°C
Max. ambient temperature (°C)	25
Power supply (V)	230
Frequency (Hz)	50/60
Power consumption (KWH/24H)	15,7
Current (A)	3,8
Weight (KG)	Check our website
Shipping weight (KG)	Check our website
Shipping weight with wooden packaging (KG)	Check our website
Shipping dimensions WxDxH (mm)	Check our website
Shipping dimensions with wooden packaging WxDxH (mm)	Check our website
No. of compressors	2
Visual / acoustic alarm	Yes
Power failure alarm	Yes
Adjustable high/low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Alarm display as text - not codes	Yes
Contact for remote alarm	Yes
Prepared for GSM alarm module	Yes
Approx. hrs of battery back up for alarms and temperature display in the event of power cut	72 hours
Porthole for installation of PT100/CO ₂ back up	Yes
Digital display	Yes
Data logger	Yes
RS 232 interface	Yes
RS 485 interface	Yes
USB up/down load	Yes
Defrost manual / auto	Manual
Castors	Yes
Chart recorder	Optional
Shelves (pcs) / drawers (pcs)	4 / *
Basket (pcs)	No
Sub door (pcs)	5
Lighting	Yes
Lock	Yes
Inner liner material	Stainless steel
Cabinet material	Varnished steel / stainless steel *
Colour (exterior)	White / stainless steel *
Refrigerant	EP88




Optional



1 The GSM alarm module sends a SMS message to one or several coded telephone numbers in case the temperature exceeds a fixed range.



2 SVS voltage stabilizers for excellent output voltage stability in case the voltage rises or drops.



3 Chart recorder for documentation of the temperature condition over a certain period of time.



4 CO₂ back up system ensures optimized safety.



5 Cryo gloves protect your hands and prevent frost bites when handling samples which are stored at down to -160 °C.

* Optional, please contact us.

We reserve the right to change specifications without notice and subject to errors.



www.arctiko.com
www.co2care.eu