

## ULUF SERIES - DUAL COOLING SYSTEM

- Dual refrigeration system
- Low energy consumption
- Low noise level
- Low heat dissipation
- Insulated inner doors
- Castors and door key lock
- Ergonomic loading
- Heated door frame
- 100% HCFC/CFC free
- Porthole for external temperature probes

## ALL STANDARD FEATURES

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Prepared for GSM alarm
- Prepared for connection of 2 additional probes
- Auto cycle in case of probe failure
- Ambient temperature display
- Direct download of logged data on USB memory stick
- Direct upload of new software via USB memory stick
- 3-level password protected
- Battery level indication
- Display text available in different languages
- Temperature graph
- Integrated data logger
- RS485/RS232 interface
- Integrated memory for 20 years
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Shows all alarms

# ULUF 750-2M

Arctiko is proud to present the true dual refrigeration system. By installing two separate cooling systems, this range adds a new dimension to your security. In the unlikely event that one system should fail, the freezer will still maintain  $-70^{\circ}\text{C}$  until the problem is solved.

**- 86 °C**

**AVAILABLE  
IN STAINLESS  
STEEL**

**ARCTIKO**

Advanced Arctiko controller

GSM alarm module for optimal safety (optional)



**Battery backup - 72 hours** ←

**Integrated data logger with memory** ←

**RS485/RS232 interface** ←

**On/off protection** ←

MODEL	ULUF 750-2M
Item code	DAI 1383
Dimensions exterior WxDxH (mm)	1030x885x1989
Capacity (L)	646
Temperature range (°C)	-86 / -40
Power supply (V)	230
Frequency (Hz)	50/60

# ARCTIKO

The art of simplicity®

# Technical specifications

Item code	DAI 1383
Dimensions exterior WxDxH (mm)	1030x885x1989
Capacity (L)	646
Dimensions interior WxDxH (mm)	790x680x1345
Insulation (mm)	120
Temperature range (°C)	-86 / -40
Max. ambient temperature (°C)	25
Power supply (V)	230
Frequency (Hz)	50/60
Power consumption (KWH/24H)	16,94
Current (A)	8,6amp
Weight (KG)	254
Shipping weight (KG)	-
Shipping weight with wooden packaging (KG)	403
Shipping dimensions WxDxH (mm)	-
Shipping dimensions with wooden packaging WxDxH (mm)	1120x940x2300
No. of compressors	2 (Dual cooling)
Visual / acoustic alarm	Yes
Power failure alarm	Yes
Adjustable high/low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Alarm display as text - not codes	Yes
Contact for remote alarm	Yes
Prepared for GSM alarm module	Yes
Approx. hrs of battery back up for alarms and temperature display in the event of power cut	72 hours
Porthole for installation of PT100/CO <sub>2</sub> back up	Yes
Digital display	Yes
Data logger	Yes
RS 232 interface	Yes
RS 485 interface	Yes
USB up/down load	Yes
Defrost manual / auto	Manual
Castors	Yes
Chart recorder	Optional
Shelves (pcs) / drawers (pcs)	4 / *
Basket (pcs)	No
Sub door (pcs)	5
Lighting	Yes
Lock	Yes
Inner liner material	Stainless steel
Cabinet material	Varnished steel / stainless steel *
Colour (exterior)	White / stainless steel *
Refrigerant	EP88


# Optional




**1** The GSM alarm module sends a SMS message to one or several coded telephone numbers in case the temperature exceeds a fixed range.



**2** SVS voltage stabilizers for excellent output voltage stability in case the voltage rises or drops.



**3** Chart recorder for documentation of the temperature condition over a certain period of time.



**4** CO<sub>2</sub> back up system ensures optimized safety.



**5** Cryo gloves protect your hands and prevent frost bites when handling samples which are stored at down to -160 °C.



CO2CARE



[www.arctiko.com](http://www.arctiko.com)

[www.co2care.eu](http://www.co2care.eu)

\* Optional, please contact us

We reserve the right to change specifications without notice and subject to errors.