ARCTIK® LF 1350

true cooling specialists



BIOMEDICAL FREEZER

With its low energy consumption, Arctiko's eco-friendly LF series offers flexibility, security, and reliability for users. The Carel controller features an integrated data logger, which can be accessed via Bluetooth.

ENERGY STAR CERTIFIED

Energy Star certified, guaranteeing exceptional energy efficiency and reduced environmental impact, while maintaining superior performance in temperaturesensitive storage applications.

▶ INTEGRATED DATA LOGGER

Combining accurate temperature monitoring for optimal sample storage and regulatory compliance, the integrated data logger empowers you with on-the-go control via detailed graphs, alarms, and settings accessible through your phone's Bluetooth connection to the unit's display.

▶ FORCED AIR COOLING

Forced air cooling provides excellent temperature stability. Forcing the airflow around the stored items ensures quick temperature recovery after door openings.

KEY LOCK SECURITY

Equipped with a secure key lock, providing an added layer of protection for valuable contents and preventing unauthorized access. This feature ensures the integrity and confidentiality of stored items, making it ideal for environments where security is paramount.

► SNAP/EPA COMPLIANT REFRIGERANT

Utilizes refrigerants that are fully compliant with the Environmental Protection Agency (EPA) and the Significant New Alternatives Policy (SNAP) regulations, ensuring environmentally responsible operation without compromising performance or safety.





DATA LOGGER



AIR FORCED COOLING



ADJUSTABLE SHELVES



VARIOUS SAFETY FEATURES



The Carel controller features Bluetooth connection, visual and acoustic alarms, high/low-temperature alarms, open-door alarms and a data logger.



Easily adjustable shelves in order to offer best flexibility for your storage needs.




All models feature durable, cost saving LED lighting for better overview of your samples.


^{*} The pictures shown are for reference only, actual product size may vary. Please read the dimensions of the product in the specifications.





The ARCTIKO PR, LR and LF series includes the following features, and more:

- Forced Air CoolingLow Energy Consumption
- Key Lock on Door
- Carel controller
- Remote Alarm Interface
- Monoblock Technology
- Eco Friendly Refrigerant









		MODEL	LF 1350
	Main specifications	Item code	1400029-01
		Temperature range (°C)	-25°C to -10°C
		Ambient temperature (°C)	40°C
		Capacity (L)	1400
		Capacity (cu.FT)	49.44
		Exterior dimensions WxDxH (inches)	57x31x79
	ain sp	Interior dimensions WxDxH (inches)	52x26x60
	Ψ	Weight (lb)	485
		Insulation (inches)	2.36
		Cooling technology	Air Forced
ļ		Controller model / probe type	Carel iJS / NTC
	Power	Power supply (V)	115
		Frequency (Hz)	60
		Power consumption (kWh/24h)	3.81
1		AMP (A)	3.2
		Power (Watt)	290
ļ		Horsepower (HP)	1/5
	Alarm functions	Alarm (displayed as text, not codes)	Yes
		Visual / acoustic alarm	Yes / Yes
		Power failure alarm	Yes
		Adjustable high / low-temperature alarm	Yes / Yes
		Open door alarm	Yes
		Probe failure alarm	Yes
ļ		Low battery alarm	Yes
	Data logging & external connection	Voltage-free contact for remote alarm (e.g. GSM alarm module)	Yes
		Electronic data logger	Yes
١		Bluetooth data download	Yes
İ		Temperature chart recorder	Optional
Ì	Display features	Lockable display to prevent accidental shutdowns	Yes
		Temperature Graph Available via app	Bluetooth
		Number of optional reference probes	2
	Other features	Automatic defrost	Yes
-		Vaccum release port	Yes
-		Access port for external probe etc.	Yes
١		Light	Yes
١		Lock with key	Yes
ļ		Castors (total pcs) / castors with brake (pcs)	6/2
ļ		Reversible door(s)	Yes
		Fixed shelves (pcs) / adjustable shelves (pcs)	6
		Max. no. of shelves (pcs) / recommended max. no. of shelves (pcs)	12
		Max load per shelf (lb)	99
İ		Adjustable drawers (pcs)	Optional
١		Max. no. of adjustable drawers (pcs)	12
		Max. load per adjustable drawer (lb)	99
	Refrigeration & cabinet	Number of compressors	1
		Refrigerant	R290
		Interior cabinet material	PVC film coated and Anticorrosion treated hot-dip Galvanized steel
		Exterior cabinet material	PVC film coated and Anticorrosion treated hot-dip Galvanized steel
		Colour (exterior cabinet)	White
		Foam type	Cyclopentane polyurethane
-		Shipping weight (lb)	531
		Shipping dimensions WxDxH (inches)	60x36x87
		Shipping volume (cu.FT)	109.48
-			



